

PUSHLITE PRO, 60M

PushLite Pro for the inspection of main sewers and property drainage pipes.
Market oriented feature set, easy to use, robust and reliable

TECHNICAL DATA PUSHLITE PRO

Application area	DN50 - DN300
Push rod length	60 m
Push rod diameter	9 mm
Material (frame/ basket)	Steel (powder coated)
Dimensions* (WxHxD)	420 x 690 x 1250 mm
Weight*	34 kg
Meter counter	Yes
Reel brake	Yes, adjustable
Interfaces Operator unit	1xLAN, 1xUSB, 1xW-LAN
External power supply	Yes
Radio standard WIFI	WIFI 2.4G
Voltage	110 - 230 VAC
Exchangeable battery Operator unit	no
Battery runtime**	Approx. 6h
Battery capacity	20.000 mAh/battery
Ambient temperature range	0 °C to 40 °C
Storage temperature range***	-10 °C to 50 °C
Protection class	IP 54
Protection class camera	IP 68



SYSTEM FEATURES

- IP 54 (with open Operator Box) for use under harsh conditions
- Wheels, integrated handle and adjustable ControlBox position
- HD picture quality, always upright picture
- Sonde frequency 512Hz

COMPATIBLE WITH:

- WinCanWeb (DataTransfer over Browser)
- Reporting in WinCanWeb / WinCanVX possible

NOT COMPATIBLE WITH:

- VC500, VC500 HD
- PTP50, PTP50 HD
- AC40, AC40 HD
- RASCON
- ATEX

*incl. push rod. without camera, batteries, control panel and trolley **battery life depending on the used control panel, camera and environmental condition. ***without batteries